





BJX-III 系列防爆接线箱(ⅡC、ⅢC)

箱体规格	导轨×接线端子(规格及数量)								出线口方向	G1/2 M20	G3/4 M25	G1 M32	G1¼ M40	G1½ M50	G2 M63
	2.5 ²	4 ²	6 ²	10 ²	16 ²	35 ²	70 ²	95 ²							
11# 	1×32	1×30	1×24	1×19	1×16	—	—	—	D/X	14	12	10	5	4	3
									L/R	14	12	10	5	4	3
14# 	1×32	1×30	1×24	1×19	1×16	—	—	—	D/X	17	15	12	6	5	4
									L/R	11	10	8	4	3	2
15# 	1×38 2×25	1×34 2×22	1×28 2×18	1×22 2×13	1×18 —	1×11 —	— —	— —	D/X	17	15	12	6	5	4
									L/R	17	15	12	6	5	4
19# 	1×60 2×45	1×54 2×40	1×44 2×30	1×34 2×25	1×26 2×20	1×15 —	1×8 —	1×8 —	D/X	24	20	16	7	6	6
									L/R	24	20	16	7	6	6

注: 1.以上参数仅供参考, 具体以图纸为准; 2.M螺纹距为1.5。

■ 外形及安装尺寸

